

PHP Fixer report

- Target: demo\site
- Generated: 2026-10-25 01:52:08 UTC
- Mode: scan only (no changes written)
- Files scanned: 10
- Findings: 31 (17 high, 4 medium, 10 low)
- Auto-fixable: 11
- Runtime: PHP 8.4.27 (verification binary) — patched against PHP2Shell (CVE-2026-109618, CVE-2026-109619)

Findings by rule

Rule	Count
dirname-file	9
removed-function	8
sql-injection	4
request-superglobal	2
header-location	2
extract	1
weak-password-hash	1
unserialize	1
dynamic-include	1
curly-offset	1
interp-braces	1

Findings

Severity	Location	Rule	What was found
high	admin/login.php:9	extract	Request array passed to extract().
high	admin/login.php:10	sql-injection	\$email carries request data into a SQL string passed to a query function.
high	admin/login.php:11	weak-password-hash	md5() applied to a value that looks like a password.
high	admin/reports.php:13	sql-injection	\$since carries request data into a SQL string passed to a query function.
high	admin/reports.php:15	unserialize	Request data is unserialized (\$_COOKIE).
high	contact.php:12	sql-injection	\$name carries request data into a SQL string passed to a query function.
high	includes/db.php:6	removed-function	mysql_connect() was removed.
high	includes/db.php:8	removed-function	mysql_error() was removed.
high	includes/db.php:10	removed-function	mysql_select_db() was removed.
high	includes/db.php:17	removed-function	mysql_query() was removed.
high	includes/db.php:19	removed-function	mysql_error() was removed.
high	includes/db.php:28	removed-function	mysql_fetch_assoc() was removed.
high	includes/db.php:36	sql-injection	\$_GET carries request data into a SQL string passed to a query function.
high	index.php:10	dynamic-include	include path is built from request data (\$page).
high	lib/util.php:6	curly-offset	\$name{0} uses a curly offset.
high	lib/util.php:12	removed-function	money_format() was removed.
high	lib/util.php:27	removed-function	get_magic_quotes_gpc() was removed.
medium	admin/reports.php:12	request-superglobal	\$_REQUEST read.
medium	contact.php:14	header-location	header("Location: ...") is not followed by exit.
medium	contact.php:24	request-superglobal	\$_REQUEST read.
medium	lib/util.php:22	header-location	header("Location: ...") is not followed by exit.

low	admin/login.php:3	dirname-file	dirname(__FILE__)
low	admin/login.php:4	dirname-file	dirname(__FILE__)
low	admin/reports.php:3	dirname-file	dirname(__FILE__)
low	admin/reports.php:4	dirname-file	dirname(__FILE__)
low	contact.php:3	dirname-file	dirname(__FILE__)
low	contact.php:4	dirname-file	dirname(__FILE__)
low	includes/config.php:11	dirname-file	dirname(__FILE__)
low	index.php:3	dirname-file	dirname(__FILE__)
low	index.php:4	dirname-file	dirname(__FILE__)
low	lib/util.php:17	interp-braces	\${who}

Detail and recommended fixes

admin/login.php:9:5 — **extract()** on request data (high)

Request array passed to extract().

Recommended fix: Read the keys you expect: \$name = \$_POST['name'] ?? '. Never extract request arrays.

admin/login.php:10:71 — **Request data concatenated into SQL (high)**

\$email carries request data into a SQL string passed to a query function.

Recommended fix: Bind the value: \$stmt = \$pdo->prepare("SELECT * FROM t WHERE id = ?"); \$stmt->execute([\$id]); Never interpolate into SQL.

admin/login.php:11:17 — **md5/sha1 used for a password (high)**

md5() applied to a value that looks like a password.

Recommended fix: password_hash(\$pw, PASSWORD_DEFAULT) on write, password_verify(\$pw, \$hash) on login. Rehash on next successful login to migrate existing users.

admin/reports.php:13:63 — **Request data concatenated into SQL (high)**

\$since carries request data into a SQL string passed to a query function.

Recommended fix: Bind the value: \$stmt = \$pdo->prepare("SELECT * FROM t WHERE id = ?"); \$stmt->execute([\$id]); Never interpolate into SQL.

admin/reports.php:15:11 — **unserialize()** on untrusted data (high)

Request data is unserialized (\$_COOKIE).

Recommended fix: Use JSON: json_decode(\$input, true). If the format is fixed, pass ["allowed_classes" => false] as the second argument.

contact.php:12:65 — **Request data concatenated into SQL (high)**

\$name carries request data into a SQL string passed to a query function.

Recommended fix: Bind the value: \$stmt = \$pdo->prepare("SELECT * FROM t WHERE id = ?"); \$stmt->execute([\$id]); Never interpolate into SQL.

includes/db.php:6:13 — **Function removed from PHP (high)**

mysql_connect() was removed.

Recommended fix: Replace with mysqli_connect or PDO.

includes/db.php:8:37 — **Function removed from PHP (high)**

mysql_error() was removed.

Recommended fix: Replace with mysqli_error(\$link).

includes/db.php:10:5 — Function removed from PHP (high)

mysql_select_db() was removed.

Recommended fix: Replace with the database name in mysqli_connect/PDO DSN.

includes/db.php:17:15 — Function removed from PHP (high)

mysql_query() was removed.

Recommended fix: Replace with mysqli_query or PDO::query.

includes/db.php:19:14 — Function removed from PHP (high)

mysql_error() was removed.

Recommended fix: Replace with mysqli_error(\$link).

includes/db.php:28:19 — Function removed from PHP (high)

mysql_fetch_assoc() was removed.

Recommended fix: Replace with \$result->fetch_assoc().

includes/db.php:36:59 — Request data concatenated into SQL (high)

\$_GET carries request data into a SQL string passed to a query function.

Recommended fix: Bind the value: \$stmt = \$pdo->prepare("SELECT * FROM t WHERE id = ?"); \$stmt->execute([\$id]); Never interpolate into SQL.

index.php:10:1 — Request data in include/require (high)

include path is built from request data (\$page).

Recommended fix: Map a request key to a fixed list of files: \$page = ['home' => __DIR__ . '/home.php']; then include \$page[\$key] ?? \$page['home'];

lib/util.php:6:19 — Curly-brace string offset (removed in PHP 8) (high)

\$name{0} uses a curly offset.

Fix applied: Use square brackets: \$str[\$i].

lib/util.php:12:12 — Function removed from PHP (high)

money_format() was removed.

Recommended fix: Replace with NumberFormatter::formatCurrency.

lib/util.php:27:9 — Function removed from PHP (high)

get_magic_quotes_gpc() was removed.

Recommended fix: Replace with stripslashes() only where input is still escaped.

admin/reports.php:12:10 — \$_REQUEST used (medium)

\$_REQUEST read.

Recommended fix: Read the intended channel: \$_GET[...] or \$_POST[...] with a default.

contact.php:14:5 — Redirect header without exit (medium)

header("Location: ...") is not followed by exit.

Recommended fix: Follow every header("Location: ...") with exit; and only redirect to a fixed or whitelisted URL.

contact.php:24:47 — \$_REQUEST used (medium)

\$_REQUEST read.

Recommended fix: Read the intended channel: \$_GET[...] or \$_POST[...] with a default.

lib/util.php:22:5 — Redirect header without exit (medium)

header("Location: ...") is not followed by exit.

Recommended fix: Follow every header("Location: ...") with exit; and only redirect to a fixed or whitelisted URL.

admin/login.php:3:14 — dirname(__FILE__) instead of __DIR__ (low)

dirname(__FILE__)

Fix applied: Replace dirname(__FILE__) with __DIR__.

admin/login.php:4:14 — dirname(__FILE__) instead of __DIR__ (low)

dirname(__FILE__)

Fix applied: Replace dirname(__FILE__) with __DIR__.

admin/reports.php:3:14 — dirname(__FILE__) instead of __DIR__ (low)

dirname(__FILE__)

Fix applied: Replace dirname(__FILE__) with __DIR__.

admin/reports.php:4:14 — dirname(__FILE__) instead of __DIR__ (low)

dirname(__FILE__)

Fix applied: Replace dirname(__FILE__) with __DIR__.

contact.php:3:14 — dirname(__FILE__) instead of __DIR__ (low)

dirname(__FILE__)

Fix applied: Replace dirname(__FILE__) with __DIR__.

contact.php:4:14 — dirname(__FILE__) instead of __DIR__ (low)

dirname(__FILE__)

Fix applied: Replace dirname(__FILE__) with __DIR__.

includes/config.php:11:9 — dirname(__FILE__) instead of __DIR__ (low)

dirname(__FILE__)

Fix applied: Replace dirname(__FILE__) with __DIR__.

index.php:3:14 — dirname(__FILE__) instead of __DIR__ (low)

dirname(__FILE__)

Fix applied: Replace dirname(__FILE__) with __DIR__.

index.php:4:14 — dirname(__FILE__) instead of __DIR__ (low)

dirname(__FILE__)

Fix applied: Replace dirname(__FILE__) with __DIR__.

lib/util.php:17:19 — \${var} interpolation (deprecated in PHP 8.2) (low)

\${who}

Fix applied: Use {\$var} inside the string.

Proposed patch (not applied)

admin\login.php

```
--- a/admin\login.php
+++ b/admin\login.php
@@ -1,7 +1,7 @@
<?php
// Admin login. Passwords were hashed with md5 before the move to PHP 8.
```

```

-require_once dirname(__FILE__) . '/../includes/config.php';
-require_once dirname(__FILE__) . '/../includes/db.php';
+require_once __DIR__ . '/../includes/config.php';
+require_once __DIR__ . '/../includes/db.php';

session_start();

```

admin\reports.php

```

--- a/admin\reports.php
+++ b/admin\reports.php
@@ -1,7 +1,7 @@
<?php
// Admin reports. Runs shell tools to export and emails the result.
-require_once dirname(__FILE__) . '/../includes/config.php';
-require_once dirname(__FILE__) . '/../includes/db.php';
+require_once __DIR__ . '/../includes/config.php';
+require_once __DIR__ . '/../includes/db.php';

session_start();
if (empty($_SESSION['uid'])) {

```

contact.php

```

--- a/contact.php
+++ b/contact.php
@@ -1,7 +1,7 @@
<?php
// Handles the contact form. Posts to itself.
-require_once dirname(__FILE__) . '/includes/config.php';
-require_once dirname(__FILE__) . '/includes/db.php';
+require_once __DIR__ . '/includes/config.php';
+require_once __DIR__ . '/includes/db.php';

$sent = false;
if ($_SERVER['REQUEST_METHOD'] == 'POST') {

```

includes\config.php

```

--- a/includes\config.php
+++ b/includes\config.php
@@ -8,6 +8,6 @@
$db_pass = 'plumb2014';
$db_name = 'rivera_site';

-$root = dirname(__FILE__);
+$root = __DIR__;
$uploads = $root . '/uploads';

```

index.php

```

--- a/index.php
+++ b/index.php
@@ -1,7 +1,7 @@
<?php
// Site entry point. Routes ?p= to a page file.
-require_once dirname(__FILE__) . '/includes/config.php';
-require_once dirname(__FILE__) . '/includes/db.php';
+require_once __DIR__ . '/includes/config.php';
+require_once __DIR__ . '/includes/db.php';

$page = $_GET['p'];

```

```
$title = 'Rivera Plumbing';
```

lib\util.php

```
--- a/lib/util.php
+++ b/lib/util.php
@@ -3,7 +3,7 @@

function initials($name)
{
-    $first = $name{0};
+    $first = $name[0];
    return strtoupper($first) . '.';
}

@@ -14,7 +14,7 @@

function greeting($who)
{
-    return "Hello ${who}, thanks for calling Rivera Plumbing.";
+    return "Hello {$who}, thanks for calling Rivera Plumbing.";
}

function redirect_back()
```

Method and limits

- Only mechanically provable rewrites are applied; anything touching business logic is reported.
- Each patched file is written to a temporary copy, checked with `php -l`, and only then replaced.
- Original bytes are kept in the backup directory; `phpfixer restore <dir>` puts them back.
- The scanner reads code, strings, comments and inline HTML separately, so matches inside comments or quoted text are not treated as code.
- A clean report is not a security guarantee: findings are pattern-level, and a manual review still applies.